

MB30™

Premium Matt Black Aluminium Foil Tape For Internal Applications

Product Description

MB30™ is a professional grade 30 micron aluminium foil tape in a matt black finish. This premium grade tape product is coated with a high performance synthetic rubber adhesive and protected by an easy release silicone paper.

Manufactured to the highest of specifications this professional matt black tape is easily conformable to irregular surfaces, providing an effective instant barrier against, heat cold, dust and moisture. MB30™ is the professional solution for the installer looking for a matt black aluminium faced tape for interior applications.

Product Data

Item	Value	Standard
Adhesive	Synthetic Rubber	
Product Thickness	30 micron	DIN EN 1942
Elongation at Break	3-5%	DIN EN 14410
Tensile Strength	1.2 N/cm	DIN EN 14410
Adhesion to Steel	32 N/25mm	DIN EN 1939
Adhesion on Background	36 N/25mm	DIN EN 1939
Temperature Stability	-20°C to 75°C	
Application Temperature	10°C to 35°C	

Markets

- Construction
- HVAC
- Process plant
- Interior Design
- Arts & Entertainment

Product Characteristics

- Matt black finish
- High quality siliconised release liner
- Available in 50, 75, 100 & 1200mm widths

Features

- Provides excellent sealing and bonding of joints and seams in HVAC ductwork applications.
- Suitable as an assembly aid for rubber system sealings.
- Excellent aging resistance for internal applications.
- Strong adhesion suitable for construction.
- Additional mechanical protection for rubber system sealings.
- Perfect for invisible repairs of matt black surfaces.

Typical Applications

Widely used by the HVAC industry in commercial or entertainment internal voids for the joining and sealing of intersections on matt black surfaces, the jointing and sealing of duct board, pipe sections and seams. Extensively used but not limited to joining and sealing of flexible air duct seams and connections, where design requirements



ProTech Global

Technical Data Sheet

are sympathetic to their environment and aesthetics are of a paramount importance.

Also used in other industrial applications requiring an adhesive tape with similar characteristics and benefits. Please check with a technical product expert to determine suitability for a particular purpose prior to use.

Storage / Shelf Life

12 months when stored in original, unopened packaging at 21°C (70°F) / 50% relative humidity, and kept out of direct sunlight.

Directions For Use:

Surface Preparation

Ensure all surfaces are dry and clean, free from dirt, dust, grease, oil, silicones or other contaminants.

Ensure firm pressure is applied to the tape to provide the best adhesive bond, and that sufficient tape is applied (of at least 25mm) either side of joints to provide a long-lasting seal.

Application

Remove the release paper from the section of MB30™ tape, taking care not to touch the adhesive surface.

Align the tape centrally over the joint. Pull the tape taut and then press down firmly over the entire joint area.

Rub the tape to remove any wrinkles or folds

Precautions in use: MB30™ Foil Tape is intended for joint sealing applications only. MB30™ is not suitable for use where the joint is subject to mechanical stress. In this instance, insulation should be fixed using a suitable adhesive or hanger system in accordance with BS5970. For further information, please contact Protech Global Ltd on +44 (0)1934 318468 or email sales@protechglobal.co.uk

The information, and, in particular, the recommendations relating to the application and end-use of ProTech Global Ltd products, are given in good faith based on ProTech Global Ltd.'s current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with ProTech Global Ltd.'s recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. ProTech Global Ltd reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

About ProTech Global Ltd

ProTech Global Ltd is a UK based company that has manufactured anti-corrosion products for over 25 years. With many years' experience in differing types of protection scenarios, ProTech Global Ltd has a reputation as a trusted supplier and partners with many corporations worldwide.

ProTech Global Ltd:

Unit 3 Lynx Crescent, Weston Industrial Estate, Weston-super-Mare, BS24 9DJ, UK

Tel: +44 (0)117 298 0573

Email: sales@protechglobal.co.uk