

Scapa D210

D210 - Double Sided Polyester Tape - Differential rubber adhesives, Clean Removal,
0.07mm

DESCRIPTION

Scapa D210 is a thin double sided tape based on a 23 micron polyester film coated on both sides with a rubber based adhesive system, protected with a 98 g/m² white paper release liner, with 0.07 mm total thickness. It is recommended for a variety of bonding, mounting and laminating applications where high plasticiser resistance is required.

APPLICATIONS

- Temporary bonding of highly plasticised PVC mats on wooden varnished flooring or existing sports floor covering.

PRODUCT BENEFITS

- Service temperature: -10°C to +70°C
- Thin bonding solution
- High shear resistance
- Extreme plasticiser resistance
- Clean removal (does not leave adhesive residue)

TECHNICAL PROPERTIES

Technical Property	Nominal Value	Unit	Test Method
Adhesion to Steel - Open Side	2.2	N/cm	AFERA 5001
Adhesion to Steel - Liner Side	4.5	N/cm	AFERA 5001
Adhesive Thickness - Open Side	0.015	mm	AFERA 5006
Adhesive Thickness - Liner Side	0.035	mm	AFERA 5006
Total Thickness (excluding liner)	0.07	mm	AFERA 5006

STANDARD PRESENTATIONS

- Colours: Transparent
- Core: 76mm Scapa branded cardboard
- Packaging: Bulk
- Roll Length: 45 metres
- Roll Width: 96 mm and 1360 mm

RECOMMENDATIONS

- The rolls should be stored flat on their cut edges in the original packaging
- The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes
- The product should be stored in temperatures between +10°C and +30°C
- Under these conditions, the storage life of the tape in a temperate climate will be 12 months
- When applied, surfaces should be clean, dry and free of dust, grease, oil or other contaminants

Get in touch:

Tema Isotech AS v/ tore@temaiso.no / +47 93 08 05 20
Kokstaddalen 26
5256 Kokstad